ANNKE NC800 Specifications Model Number: I91BQ		
Camera	Image Sensor	1/1.2" Progressive Scan CMOS
	Video Resolution	50 Hz: 20 fps (3840 X 2160, 3072 X 1728) 25 fps (2688 X 1520, 1920 X 1080, 1280 X 720) 60 Hz: 20 fps (3840 X 2160, 3072 X 1728) 30 fps (2688 X 1520, 1920 X 1080, 1280 X 720)
	Sub Stream	50 Hz: 25 fps (640 X 480, 640 X 360, 320 X 240) 60 Hz: 30 fps (640 X 480, 640 X 360, 320 X 240)
	Video Compression	Main Stream: H.265/H.264/H.264+/H.265+ Sub-Stream: H.265/H.264/MJPEG Third Stream: H.265/H.264
	Video Bitrate	32 Kbps — 16 Mbps
	Audio Compression	G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/MP3/AAC
	Audio Input/Output	Built-in Microphone
	Lens	2.8 mm
	Min. Illumination	0.0005 Lux @ (F1.0, AGC On), 0 Lux with Light
	Angle of View	Horizontal FoV 102°, Vertical FoV 52°, Diagonal FoV 124°
	Number of Warm Light	1
	Night Vision Distance	Up to 130 ft/40 m
	Image Enhancement	BLC, HLC, 3D DNR
	Wide Dynamic Range	130 dB WDR
	Network Storage	MicroSD/SDHC/SDXC card (256 GB) Local Storage, and NAS (NFS, SMB/CIFS)
	Face Capture	Yes
	Perimeter Protection	Line Crossing Detection, Intrusion Detection, Region Entrance Detection, Region Exiting Detection
	Smart Event	Motion Detection 2.0 (Human and Vehicle), Line Crossing Detection, Intrusion Detection
	ONVIF	Support
	Day/Night Switch	Day, Night, Auto, Schedule
	Ethernet	RJ45 X1 (10 M/100 M)
General	Housing	Front Cover: Metal, Back Cover: Metal
	Color	White
	Operating Power	PoE 802.3af, Class 3), 12 V DC ± 25%
	Storage	MicroSD/SDHC/SDXC card (256 GB) local storage &NAS (NFS, SMB/CIFS), ANR
	Hardware Reset	Yes
	Operating Temperature	-22 °F – 140 °F/-30 °C – 60 °C
	Indoor/Outdoor	Indoor/Outdoor
	Weatherproof Rating	IP67
	Dimension (L X W X H)	78.8 X 78.6 X 215.2 mm (3.1'' X 3.1'' X 8.5'')
	Weight	1.9 lbs./860 g